

Prüfen · Überwachen · Zertifizieren

Certificate of constancy of performance 0432-CPR-00143-01

Version 05

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Door Coordinator IS for the Swing Door System GEZE Powerturn F

Door Coordinator for double-leaf-doors accroding to the combination and classification in Appendix 2

placed on the market under the name or trade mark of

GEZE GmbH

Reinhold-Vöster-Straße 21-29 71229 Leonberg, Germany

and produced in the manufacturing plant(s)

DO 14.1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)

EN 1158:1997/A1:2002/AC:2006

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 15.01.2020 and will remain valid until 15.01.2025 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 15th January 2020



By order

Dipl.-Ing. Friedrich Head of Certification Body

This Certificate consists of 1 page and 2 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00143-01 dated

18.10.2018, Version 04.

DAKKS

Deutsche
Akkreditierungsstelle
D-ZE-11142-01-01

The original of this document was issued in German language.
In case of doubt only the German version is valid.



Prüfen · Überwachen · Zertifizieren

GEZE Door Coordinator IS

Manufacturing plant

Product	Manufacturing plant
Door coordinator	GEZE GmbH
	Reinhold-Vöster-Str.21-29
	71229 Leonberg, Germany
	DO 14.1

Annex 1 to Page 1 of 1



Prüfen · Überwachen · Zertifizieren

List of Products

Type: Door Coordinator IS for the swing door system GEZE Powerturn F.

Description: Door Coordinator IS for double-leaf-doors in combination with swing

door systems.

Door closing device active-/inactive leaf:Swing door system "GEZE Powerturn F-IS" or

Swing door system "GEZE Powerturn F/R-IS"

Arm system: scissor arm, optional with axis extensions of 30/50 mm

Installation: Frame fixing, push side according to manufacturer specifications

Size: 6 - 7

Classification: 3 8 6-7 1 1 0

Manufacturing plant: DO 14.1

Remarks: with mounting plate. The carry bars "GEZE CB Flex" or "Dictator MK90"

are always needed, if the mechanical closing sequence of both door leafs

is not achieved.

Type: Door Coordinator IS for the swing door system GEZE Powerturn F.

Description: Door Coordinator IS for double-leaf-doors in combination with swing

door systems.

Door closing device active-/inactive leaf: Swing door system "GEZE Powerturn F-IS" or

Swing door system "GEZE Powerturn F/R-IS"

Arm system: slide channel arm (assembly), optional with axis extension of 30/50 mm

and roll pin of 23 mm

Installation: Frame fixing, push side according to manufacturer specifications

Size: 4 - 6

Classification: 3 8 4-6 1 1 0

Manufacturing plant: DO 14.1

Remarks: with mounting plate. The carry bars "GEZE CB Flex" are always needed, if

the mechanical closing sequence of both door leafs is not achieved.

Type: Door Coordinator IS for the swing door system GEZE Powerturn F.

Description: Door Coordinator IS for double-leaf-doors in combination with swing

door systems.

Door closing device -/inactive leaf:Swing door system "GEZE Powerturn F-IS" or

Swing door system "GEZE Powerturn F/R-IS"

Arm system: slide channel arm (assembly), optional with axis extension of 30/50 mm

and roll pin of 23 mm

Installation: Frame fixing, pull according to manufacturer specifications

Size: 4 - 6

Classification: 3 8 4-6 1 1 0

Manufacturing plant: DO 14.

Remarks: with mounting plate. The carry bars "GEZE CB Flex" or "Dictator MK90"

are always needed, if the mechanical closing sequence of both door leafs

is not achieved.



Prüfen · Überwachen · Zertifizieren

Intended use:

For single and double leaf fire- and/or smoke protection swingdoors

Essential property	Sections with requirements in EN 1158:1997/A1:2002/AC:2006	Performance of the product
Self-closing	5.1.2 Completeness of products	passed
	5.1.3 Correct closing sequence	passed
	5.2.1 General	passed
	5.2.2 Overload behaviour in the closing direction	passed
	5.2.3 Manipulation	passed
	5.2.4 Resistance of the waiting position	passed
	5.2.6 Damage	passed
	5.2.8 Suitability for fire / smoke protection doors	Class 1: passed
Durability of	5.2.5 Durability	Class 8 (500.000 cycles): Passed
Self-closing	5.2.7 Corrosion resistance	
	5.2.7.1	Class 0: not required
	5.2.7.2	Class 0: not required
	5.2.7.3	Class 0: not required
Dangerous	Annex ZA.3	The manufacturer has not declared any dangerous
substances		substances.

Annex 2 to Page 2 of 4



Prüfen · Überwachen · Zertifizieren

List of Products

Type: Door Coordinator IS for the swing door system GEZE Powerturn F and

the door closer GEZE TS 4000.

Description: Door Coordinator IS for double-leaf-doors in combination with swing

door systems.

Door closing device active leaf: Swing door system "GEZE Powerturn F-IS" or

Swing door system "GEZE Powerturn F/R-IS"

Door closer device inactive leaf: door closer "GEZE TS 4000 EN 5-7" (with door closer size range 5 to 7)

or "GEZE TS 4000" (with door closer size range 1 to 6)

Arm system: scissor arm

Installation: Frame fixing, push side according to manufacturer specifications

Size: 6 - 7

Classification: 3 5 6-7 1 1 0

Manufacturing plant: DO 14.1

Remarks: with mounting plate. The carry bars "GEZE CB Flex" or "Dictator MK90"

are always needed, if the mechanical closing sequence of both door leafs

is not achieved.

Type: Door Coordinator IS for the swing door system GEZE Powerturn F and

the door closer GEZE TS 5000 L.

Description: Door Coordinator IS for double-leaf-doors in combination with swing

door systems.

Door closing device active leaf: Swing door system "GEZE Powerturn F-IS" or

Swing door system "GEZE Powerturn F/R-IS"

Door closer device inactive leaf: door closer "GEZE TS 5000 L" (with door closer size range 2 to 6)

Arm system: slide channel arm (assembly)

Installation: Frame fixing, pull side according to manufacturer specifications

Size: 4 - 6

Classification: 3 5 4-6 1 1 0

Manufacturing plant: DO 14.1

Remarks: with mounting plate. The carry bars "GEZE CB Flex" or "Dictator MK90"

are always needed, if the mechanical closing sequence of both door leafs

is not achieved.



Prüfen · Überwachen · Zertifizieren

Intended use:

For single and double leaf fire- and/or smoke protection swingdoors

Essential property	Sections with requirements in EN 1158:1997/A1:2002/AC:2006	Performance of the product
Self-closing	5.1.2 Completeness of products	passed
	5.1.3 Correct closing sequence	passed
	5.2.1 General	passed
	5.2.2 Overload behaviour in the closing direction	passed
	5.2.3 Manipulation	passed
	5.2.4 Resistance of the waiting position	passed
	5.2.6 Damage	passed
	5.2.8 Suitability for fire / smoke protection doors	Class 1: passed
Durability of	5.2.5 Durability	Class 5 (50.000 cycles): Passed
Self-closing	5.2.7 Corrosion resistance	
	5.2.7.1	Class 0: not required
	5.2.7.2	Class 0: not required
	5.2.7.3	Class 0: not required
Dangerous substances	Annex ZA.3	The manufacturer has not declared any
		dangerous substances.

Annex 2 to Page 4 of 4