

# Product data sheet F 1200 basic hardware \*



Cranked turn-and-tilt hardware for manual ventilation of rooms and staircases

## **AREAS OF APPLICATION**

- ightarrow Ventilation of rooms and stairways
- ightarrow Large and heavy windows up to 200 kg leaf weight
- ightarrow Inward-opening rectangular windows with bottom-hung and side-hung leaves
- $\rightarrow$  Outward-opening top-hung leaf:
- ightarrow Installation on wooden, PVC or metal windows
- ightarrow Leaf installation



#### **PRODUCT FEATURES**

- ightarrow Ventilation with variable adjustment from gap ventilation to the tilted end position
- ightarrow Functional safety due to weight-independent crank handle activation with control display
- ightarrow Additional protection against incorrect operation and overload friction coupling
- ightarrow Secure locking due to the arrangement of virtually any number of bolt positions on all four sides
- ightarrow All fitting parts are positioned on the inner leaf shell

#### **TECHNICAL DATA**

Productname	F 1200 basic hardware *		
Leaf width (min.)	750 mm		
Leaf height (min.)	750 mm		
Leaf weight (max.)	200 kg		

### VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Installed position	Leaf width (min.)
F 1200 basic hardware *	without gear, for vertical gear installation / Cranked turn- and-tilt hardware for manual ventilation of rooms and staircases	062910	silver- coloured	left	750 mm
F 1200 basic hardware *	without gear, for vertical gear installation / Cranked turn- and-tilt hardware for manual ventilation of rooms and staircases	062908	silver- coloured	right	750 mm

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.