

# Product data sheet

## Boxer EFS 4-6



Integrated door closer for 1-leaf doors with a leaf width of up to 1400 mm with electric free swing

### AREAS OF APPLICATION

- Fire and smoke protection doors, proof of suitability for the door required
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width and 180 kg leaf weight
- Integrated installation
- Hold-open systems with integrated hold-open function with free swing
- Barrier-free access in accordance with DIN 18040

# Boxer EFS 4-6



## PRODUCT FEATURES

- Closing force with variable adjustment of EN 4-6
- Can be used for right and left hand doors without conversion
- Door closer is embedded in the door leaf and frame and fulfils the highest design demands
- Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
- Free swing function makes it possible to pass through the door with little physical force required
- Comfort hold-open function locks the door at the end of the free swing area
- Smoke switch control unit can be connected, whose signal makes the door close automatically in the event of a fire
- Integrated back check, slows down doors that are thrown open forcefully
- Hydraulic latching action which accelerates the door shortly before it is closed
- Closing speed can be individually adjusted
- All functions can be adjusted in the installed state

## TECHNICAL DATA

Productname	Boxer EFS 4-6
Closing force in accordance with EN 1154	EN 4 - 6
Barrier-free in accordance with DIN 18040 up to leaf width (max.) in mm	1400 mm
Leaf width (max.)	1400 mm
Leaf weight (max.)	180 kg
Type of installation	Concealed
Opening angle (max.)	120 °
Input voltage	24 V DC
Suitability for fire protection doors	Yes
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Back check integrated	Mechanically in the guide rail
Position of closing force adjustment	Top
Hold-open function	Electrically, for free-swing function
Smoke switch integrated	No

## Boxer EFS 4-6



---

### PART

#### CLOSER BODY BOXER EFS 4-6

Main body for integrated door closer size EN 4-6 with electric free swing function incl. free swing lever with comfort hold-open function



---

#### Designation

Boxer EFS 4-6

---

#### GUIDE RAIL BOXER EFS 20.7 MM

With an overall height of 20.7 mm for Boxer EFS 4-6



---

#### Designation

Guide rail Boxer EFS 20.7 mm

---

#### GUIDE RAIL BOXER EFS 12 MM \*

With an overall height of 12 mm for Boxer EFS 4-6



---

#### Designation

Guide rail Boxer EFS 12 mm

---


## Boxer EFS 4-6



### ACCESSORIES

#### SPINDLE EXTENSION BOXER EFS 4-6 \*

For comfort hold-open lever



#### Designation

Spindle extension Boxer EFS 4-6

Spindle extension Boxer EFS 4-6 \*

#### GC 152 \*

Smoke detector for GEZE hold-open systems



#### Designation

GEZE smoke detector GC 152 \*

#### GC 153 \*

Thermal detector for GEZE hold-open systems



#### Designation

GEZE thermal detector GC 153 \*

## Boxer EFS 4-6



### AS 500

Manual trigger switch for the manual release of electrically controlled hold-open devices



#### Designation

AS 500 manual trigger switch

AS 500 manual trigger switch, glass

### RSZ 7 \*

Extendable smoke switch control unit for all GEZE hold-open devices



#### Designation

RSZ 7 smoke switch control unit \*

RSZ 7 smoke switch control unit \*

RSZ 7 smoke switch control unit \*

RSZ 7 smoke switch control unit \*

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.