

Product data sheet

ISM guide rail BG VPK TS 5000 complete CB flex *



Overhead door closer system with guide rail, for opposite hinge side, for double leaf doors with anti-panic function and closing sequence control

AREAS OF APPLICATION

- Fire and smoke protection doors
- Double leaf single-action doors with panic function
- Symmetrical and asymmetrical division of door possible
- Single-action doors up to 2800 mm hinge clearance and 1400 mm leaf width
- Door weight up to 180 kg
- Door leaf installation opposite hinge side

ISM guide rail BG VPK TS 5000 complete CB flex *



PRODUCT FEATURES

- Complete package with two TS 5000 L and TS 5000 L-IS door closers with ISM guide rail
- Closing force of EN2-6 with variable adjustment
- Can be used for right and left hand doors without conversion
- Full panic function on both door leaves up to x dimension 110 mm
- Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
- Hydraulic latching action which accelerates the door shortly before it is closed
- Closing speed can be individually adjusted
- Integrated back check, slows down doors that are thrown open forcefully
- Visual closing force display for easy control of the setting
- All functions can be adjusted from the front

TECHNICAL DATA

Productname	ISM guide rail BG VPK TS 5000 complete CB flex *
Leaf width (max.)	1400 mm
Identical design for DIN left and DIN right	Yes
Minimum hinge clearance	1300 mm
Minimum passive leaf width	380 mm
Standard conformity	EN 1154:1996/A1:2002/AC:2006, EN 1158
Length	2730 mm
Width	55 mm
Height	30 mm
Smoke switch integrated	No
Closing sequence control integrated	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident- No.	Colour	Closing force in accordance with EN 1154	Dime nsion s
TS 5000 L- ISM VPK *	System solution for general use on full panic doors consisting of 1 x TS 5000 L, 1 x TS 5000 L- IS, 1 x CB flex, 1 x ISM BG guide rail, continuous, with integrated release mechanism and levers	182650	white RAL 9016		
TS 5000 L- ISM VPK *	System solution for general use on full panic doors consisting of 1 x TS 5000 L, 1 x TS 5000 L- IS, 1 x CB flex, 1 x ISM BG guide rail, continuous, with integrated release mechanism and levers	182642	silver- coloured		

ISM guide rail BG VPK TS 5000 complete CB flex *



Designation	Description	Ident- No.	Colour	Closing force in accordance with EN 1154	Dime nsion s
TS 5000 L- ISM VPK *	System solution for general use on full panic doors consisting of 1 x TS 5000 L, 1 x TS 5000 L- IS, 1 x CB flex, 1 x ISM BG guide rail, continuous, with integrated release mechanism and levers	182643	according to RAL		

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.