Product data sheet

NOT 220 AP *

RWS emergency push button for opening a sliding or swing door in an emergency

AREAS OF APPLICATION

- Indirect release of GEZE emergency exit system door control units
- Opening of automatic doors in case of an emergency
- Surface-mounted installation for simple installation without a lot of effort
- Outdoors thanks to high IP rating

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-14T04:21:32Z

NOT 220 AP *

PRODUCT FEATURES

- LED lighting for better visibility, even in the dark
- Contact system consists of one normally closed contact and one normally opened contact
- A second normally closed contact is available as an accessory
- Robust plastic housing protects the emergency push button reliably from mechanical effects

TECHNICAL DATA

	NOT 220 AP *
Dimensions	94 x 94 x 122 mm
Supply voltage	24 V DC
Current consumption	15 mA
IP rating	IP65
Type of installation	Surface-mounted
Service temperature	-25 - 70 °C

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	Operating voltage	Type of installation
NOT 220 AP emergency push button, IP65	in plastic casing IP65; 94 x 94 x 122 mm; with emergency exit sign arrow downwards; Operating voltage: 24 V DC; Contact rating: 3A, 250 V; 1 normally closed contact	210203	94 x 94 x 122 mm	24 V DC	Surface-mounted

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.